

Commissioner for Patents
Response to March 31, 2004 Office Action
Filed July 30, 2004 via facsimile transmission
Page 4 of 13

Serial: 09/779362
Art Unit: 2154
Examiner: H. Patel
Docket: AUS9 2000 0522 USI

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1 (currently amended). A data processing network, comprising:

a first server connected to a central switch;

a second server connected to the switch, wherein the second server includes a network interface card (NIC) enabled to receive management protocol data units (PDUs) from the first server and application PDUs from an external network; and

wherein the NIC is configured to buffer the management PDUs and the application PDUs and to initiate host processing of the management PDUs by asserting a first interrupt and to initiate host processing of the application PDUs by asserting a second interrupt and further wherein the NIC is configured to interpret priority information in the management and application PDUs {and-enabled} to prioritize the first and second interrupts {to a host processor of the second server} based upon the priority information.

2 (currently amended). The network of claim 1, wherein the second server ~~{includes a}~~ host processor is connected to {a network interface card} NIC and wherein the ~~{second server}~~ NIC is configured to buffer the management PDUs and application PDUs in a buffer on the NIC.

3 (original). The network of claim 1, wherein the second server is further configured to generate application PDUs destined for the external network and management PDUs destined for the first server responsive to the received PDUs.

4 (currently amended). The network of claim 3, wherein the management PDUs include a single packet header, {are} generated at a low level of the network's communication protocol stack.

5 (currently amended). The network of claim 4, wherein the communication protocol stack comprises a TCP/IP protocol stack and further wherein the application PDUs comprise ~~{TCP/IP}~~ PDUs having TCP/IP headers and the single packet header of the management PDUs are generated at a data link level of the stack.

6 (currently amended). The network of claim ~~{4}~~ 4, wherein the data link level of the communication protocol stack is a MAC level and wherein the priority information is included in an IEEE 802.1q compliant header of the PDUs.

7 (original). The network of claim 1, wherein the second server is configured to grant higher priority to application PDUs than management PDUs.

Commissioner for Patents
Response to March 31, 2004 Office Action
Filed July 30, 2004 via facsimile transmission
Page 5 of 13

Serial: 09/779362
Art Unit: 2154
Examiner: H. Patel
Docket: AUS9 2000 0522 US1

8 (original). The network of claim 7, wherein the second server NIC is configured to buffer management PDUs until a management PDU interrupt is issued.

9 (original). The network of claim 8, wherein the second server NIC is further configured to issue a management PDU interrupt after detecting an absence of management PDU activity for a predetermined interval.

10 (original). The network of claim 1, wherein the second server comprises a server appliance and wherein the network further includes a plurality of additional server appliances each attached to the switch.

11 (original). The network of claim 10, wherein the first server comprises a management server enabled to manage each of server appliances.

12 (currently amended). A method of handling protocol data units (PDUs) in server appliance of a data processing network, comprising:

receiving an application PDU from an external network and buffering the application PDU;

interpreting priority information contained in the application PDU;

receiving a management PDU from a management server of the data processing network and buffering the management PDU;

interpreting priority information contained in the management PDU; ~~and~~

prioritizing first and second interrupts ~~{to a host processor of the server appliance}~~ based upon the priority ~~{information}~~ information; and

interrupting the host processor with the first interrupt to service the application PDUs and
interrupting the host processor with the second interrupt to service the management PDUs.

13 (currently amended). The method of claim 12, wherein receiving an application PDU comprises receiving ~~{a TCP/IP formatted}~~ an application PDU having a TCP/IP header and wherein receiving the management PDU comprises receiving a ~~{low-level}~~ management PDU having, as its exclusive header, a MAC header.

14 (original). The method of claim 12, wherein interpreting priority information includes identifying priority bits in a data link header of the received PDUs wherein the header is compliant with IEEE 802.1q.

Commissioner for Patents
Response to March 31, 2004 Office Action
Filed July 30, 2004 via facsimile transmission
Page 6 of 13

Serial: 09/779362
Art Unit: 2154
Examiner: H. Patel
Docket: AUS9 2000 0522 US1

15 (canceled). ~~The method of claim 12, further comprising interrupting the host processor with a first interrupt to service the application PDUs and interrupting the host processor with a second interrupt to service the management PDUs.~~

16 (currently amended). The method of claim ~~{15}~~ 12, wherein prioritizing the host processor interrupts includes granting higher priority to the applications PDUs than to the management PDUs.

17 (original). The method of claim 16, wherein interrupting the host processor to service the management PDUs includes interrupting the host processor responsive to detecting an absence of application PDU activity for a predetermined duration.

18 (currently amended). A server appliance suitable for use in a data processing network, comprising:

a host processor connected to a host memory;

a network interface card (NIC) connected to the host processor and enabled to connect to and communicate with a central switch of the data processing network;

wherein the NIC is further configured to receive and buffer management PDUs and application PDUs and to initiate host processing of the management PDUs by asserting a first interrupt and to initiate host processing of the application PDUs by asserting a second interrupt and further wherein the NIC is configured to interpret priority information contained in the application {protocol data units received from an external network} PDUs and {in} the management PDUs {received from a management server connected to the switch,} and wherein the NIC is further configured to prioritize the first and second interrupts to the host processor based upon the priority information in the received PDUs.

19 (original). The server appliance of claim 18, wherein the server appliance is further configured to generate application PDUs destined for the external network and management PDUs destined for the first server responsive to the received PDUs.

20 (currently amended). The server appliance of claim 19, wherein the management PDUs ~~{are}~~ comprise PDUs having a single header, wherein the single header is generated at a {low} data link level of the network's communication protocol stack.

21 (currently amended). The server appliance of claim 20, wherein the communication protocol stack comprises a TCP/IP protocol stack and further wherein the application PDUs comprise ~~{TCP/IP}~~ PDUs having TCP/IP headers and the management PDUs are ~~{generated at a data link level of the stack}~~ PDUs having a MAC header.

22 (original). The server appliance of claim 18, wherein the server appliance is configured to grant higher priority to application PDUs than management PDUs.

*Commissioner for Patents
Response to March 31, 2004 Office Action
Filed July 30, 2004 via facsimile transmission
Page 7 of 13*

*Serial: 09/779362
Art Unit: 2154
Examiner: H. Patel
Docket: AUS9 2000 0522 US1*

23 (original). The server appliance of claim 22, wherein the server appliance NIC is configured to interrupt the host processor on each received application PDU and to buffer management PDUs until a management PDU interrupt is issued.

24 (original). The server appliance of claim 23, wherein the server appliance NIC is further configured to issue a management PDU interrupt after detecting an absence of management PDU activity for a predetermined interval.